

INDOOR OR OUTDOOR APPLICATION

**INDUSTRIAL STRENGTH
ENVIRONMENTALLY SAFE**

CGR

COATING REMOVER

NATURAL CITRUS FRAGRANCE

COATING AND GRAFFITI REMOVER

- ✓ *Removes polyurethanes, epoxies & graffiti from porous surfaces*
- ✓ *Restores without damage*
- ✓ *Removes ghosting & stains*



 **eco**
coating systems
surface preparation & maintenance
products for industry professionals

✓ **NON-TOXIC** ✓ **NON-CORROSIVE** ✓ **NON-FLAMMABLE** ✓ **BIODEGRADABLE**

RECOMMENDED SURFACES FOR APPLICATION

Aluminium
Bitumen
Canvas
Concrete
Colour Bond
High Solids Epoxy
Fibreglass

Galvanised Iron
Gel Coat
Glass
Grout
Laminate
Linoleum
Masonry

Metals
Plastic
Polyurethane
Tiles
Timber
Vinyl
Zincalume

Product Description

- Industrial strength & easy to use as it removes coatings and graffiti.
- Multi functional, fast acting, low odour, slow drying, free rinsing and is suitable on warm surfaces. Ideal for indoor or outdoor application. With natural citrus solvents.
- More user friendly to operator, minimises need for protective clothing, requires low pressure water rinse only.

Limitations

- Will not remove some high solids or chemical resistant coatings.
- Should not be applied when inclement weather is imminent.
- A test area should always be done to verify compatibility with substrate.

Application

- Apply GR so as to wet surface thoroughly by broom, brush or spray.
- Dwell time will be dependant on coating and graffiti build or thickness. If too heavy may have to repeat application.
- If product gets absorbed or dries out reapply to required areas.
- Generally 1-20 minutes will remove general coatings and graffiti, however, each case is different and will have to be tested for dwell times etc.
- Use high/low pressure rinse being careful not to damage the substrate.

Coverage

- Coverage is dependent on the surface porosity and texture, as a guide 1 litre will cover approximately 2 -10 sqm.

Cleanup

- Use soapy water to clean up equipment.

Emergency & First Aid Procedures

Ingestion: If swallowed do not induce vomiting, give water and seek medical advice.

Eye: Hold eyes open and flood with plenty of water for at least 15 minutes. Seek medical advice.

Skin: Remove contaminated clothing and wash affected area with copious quantities of water.

Inhalation: Remove affected person from contaminated area and seek medical advice.

Advice to Doctor

- Treat symptomatically

Storage and Handling

- Protect against physical damage. Store in a cool, dry well ventilated location.

Transportation

- Not classified as a Dangerous Good by Criteria of the Australian Dangerous Goods Code.

CAUTION

KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS
BEFORE OPENING OR USING

Acrylic

Primers

Oil Paint

Acrylic Enamel

Epoxy

Aerosol Paint

Adhesives

Polyurethane

Tyre Marks

Bond Breakers

Clear Sealers

Grey Timber

Enamel

Lacquers

Wax

2 Pack Enamels

Tar

Solvent Markers

Colour Sealers

Pen Ink

ECO COATING SYSTEMS
PO BOX 2141,
NOOSAVILLE BC 4566
T.0419 150 814
E.tmmmax@bigpond.com
W.ecocoatingsystems.com.au

 **eco**
coating systems
surface preparation & maintenance
products for industry professionals

✓ NON-TOXIC ✓ NON-CORROSIVE ✓ NON-FLAMMABLE ✓ BIODEGRADABLE